

3.5.11 Labels. Commercially produced labels, white or other appropriate color, having all specified marking permanently printed or otherwise marked on them. Marking shall be easily read and sized to suit the application. Such labels shall be plastic or metal and are normally adhesively mounted. The labels and their mounting are to resist aggressive atmospheres and/or liquids which may occur in the application. When such labels are mounted, appropriate care in cleaning or otherwise preparing the surface is required. Recommendations of the manufacturer are to be followed where appropriate.

- a. Possible Source. Multiple .....
- b. Typical Use. Smooth metal surfaces, plated or painted.

#### 4.0 QUALITY ASSURANCE PROVISIONS

##### 4.1 Inspection

All markings shall be visually inspected for conformance with the requirements of this specification. The following qualities should be considered.

- a. Conformance to the applicable drawing.
- b. Good definition.
- c. Complete legibility.

##### 4.2 Adhesion and Smear

4.2.1 Samples. Qualification samples and samples subjected to environmental tests shall be tested per 4.2.2 before and after the tests.

4.2.2 Testing. All specified markings shall be rubbed a total of 20 strokes in one direction only with a clear dry thumb using normal firm pressure. There shall be no evidence of deterioration of the marking.

#### 5.0 PREPARATION FOR DELIVERY

This section not applicable to this specification.

#### 6.0 NOTES

This section not applicable to this specification.